RoHS Compliant | Customer Drawing

REV.	ECN NO.	DESCRIPTION	DATE	DESIGN











PCB LAYOUT(RECOMMENDED)

(TOP VIEW TOL. :±0.05)

N=No.of contacts

SPECIFICATION

MATERIAL

- Housing:PA66,UL94V-0
- Pin Header:Brass,Tin Plated

ELECTRICAL

- Rated voltage:300V
- Rated current: 8A
- Withstanding voltage: AC2000V/ 1Min

MECHANICAL

- Strip Length:10mm
- Operating Temperature:-40°C~+105°C

订购方式/HOW TO ORDER



Contact Us

TEL:+86－574－63510149 FAX:+86－574－63516735

E-Mail:Sales@cxsuteng.com Website:www.cxsuteng.com

公差一览表 TOLERANCE UNLESS OTHERWISE			
X.	±0.25	X°.	±5°
.X	±0.20	.X°	±2°
.XX	±0.15	.XX°	±1°
.XXX	±0.02	.XXX°	±0.5°
日期 DATE	2012. 07. 10		

慈溪市速腾电子有限公司 SUTOWN CIXI SUTENG ELECTRONIC CO., LTD

单位 UNITS	mm	制图 DRAWING	No.01	产品名称 TITLE	ST15EDGVCM-3.5/3.81
角法 VIEW		设计 DESIGN	No.06		
比例 SCALE	1:1	审核 CHKD		产品料号 PART NO.	ST15EDGVCM-3.5/3.81
版本 VER	A0	核准 APPD		图号 DRAW NO.	ST15EDGVCM-3.5/3.81